

CAMSO SKS 793S



SKID STEER
LOADERS



SEVERE-DUTY AND FLAT-FREE

Next-generation versatile solid tire solution. Engineered to deliver excellent ride quality and best durability for mixed- and hard-surface skid steer applications.

camso.co

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



CAMSO SKS 793S



INNOVATIVE NON-DIRECTIONAL TREAD PATTERN

- Provides greater durability and versatility for mixed and hard surface applications

NEW ELONGATED APERTURE DESIGN

- Provides excellent ride quality and reduces cracking

REUSABLE WHEEL


- Provides lower cost per hour and quicker installation

MASSIVE TREAD DEPTH

- Improves durability for longer service life

TIRE SIZE	RIM SIZE	ACTUAL TIRE DIMENSIONS			HEEL		LOAD CAPACITY [kg] [lb]						
							Counterbalanced lift trucks			Other vehicles			Static
		O.D. [mm] [in]	O.W. [mm] [in]	O.T.D. [mm] [32nd]	Load wheel		Steering wheel		6 km/h 4 mph	10 km/h 6 mph	25 km/h 16 mph	0 km/h 0 mph	
					Normal	Quick	15 km/h 9 mph	25 km/h 16 mph					25 km/h 16 mph
31x10-20 (10-16.5)	7.50	780	233	39	-	■	-	4030	3100	4030	3660	3100	4680
		30.7	9.2	49	-	■	-	8885	6835	8900	8100	6850	10350
33x12-20 (12-16.5)	7.50	830	285	39	-	■	-	5200	4000	5200	4720	4000	6040
		32.7	11.2	50	-	■	-	11465	8820	11500	10400	8850	13350
36x14-20 (14-17.5)	7.50	910	322	52	-	■	-	6175	4750	6175	5605	4750	7175
		35.8	12.7	66	-	■	-	13650	10500	13650	12350	10500	15850

EXTRAPOLATED TREAD LIFE COMPARISON



Internal testing under controlled conditions demonstrated a 40% tread life advantage over a competitor's solid skid steer tire.

AUTHORIZED DISTRIBUTOR:

camso.co



VORMALS CAMOPLAST SOLIDEAL