

MS601 SM

Press-on Band Solid Tires

PREMIUM SMOOTH



- High energy efficiency
- Excellent heat dissipation
- Full tread profile for uniform load distribution
- Wide Footprint for maximum stability
- Meets TRA and ETRTO global design standards
- Long lasting smooth pattern
- Outstanding chunk and tear resistance
- Premium natural rubber compounds:
 - Low Rolling Resistance (LRR)
 - Chunk Resistant Non-Marking
- Available in both marking and non-marking

Applications



Footprint



Size	Load Capacity (kg)						Unit	Tire Dimensions	
	10 km/h		15 km/h		25 km/h			Section Width	Overall Diameter
	Load Wheels	Steer Wheels	Load Wheels	Steer Wheels	Load Wheels	Steer Wheels			
9 x 5 x 5 (229 x 127 x 127)	960	790	855	715	695	570	in.	5.0	9.0
							mm	127	229
10 x 5 x 6 1/2 (254 x 127 x 165)	1010	830	905	760	735	605	in.	5.0	10.0
							mm	127	254
13 1/2 x 5 1/2 x 8 (343 x 140 x 203)	1510	1240	1345	1130	1095	895	in.	5.5	13.5
							mm	140	343
14 x 4 1/2 x 8 (356 x 127 x 254)	1170	960	1045	875	850	695	in.	4.5	14.0
							mm	127	356
15 x 5 x 11 1/4 (381 x 127 x 285.8)	1390	1140	1240	1040	1010	830	in.	5.0	15.0
							mm	127	381
16 x 5 x 10 1/2 (406 x 127 x 266.7)	1510	1240	1345	1130	1095	895	in.	5.0	16.0
							mm	127	406
16 x 6 x 10 1/2 (406 x 152 x 266.7)	1910	1570	1710	1435	1390	1140	in.	6.0	16.0
							mm	152	406
16 x 7 x 10 1/2 (406 x 178 x 266.7)	2325	1910	2070	1740	1685	1380	in.	7.0	16.0
							mm	178	406
16 1/4 x 5 x 11 1/4 (413 x 127 x 285.8)	1530	1250	1360	1145	1105	905	in.	5.0	16.3
							mm	127	413
16 1/4 x 6 x 11 1/4 (413 x 152 x 285.8)	1920	1580	1715	1440	1395	1140	in.	6.0	16.3
							mm	152	413
16 1/4 x 7 x 11 1/4 (413 x 178 x 285.8)	2325	1900	2060	1735	1680	1380	in.	7.0	16.3
							mm	178	413
18 x 5 x 12 1/8 (457 x 127 x 308)	1640	1350	1470	1230	1195	980	in.	5.0	18.0
							mm	127	457



Size	Load Capacity (kg)						Unit	Tire Dimensions	
	10 km/h		15 km/h		25 km/h			Section Width	Overall Diameter
	Load Wheels	Steer Wheels	Load Wheels	Steer Wheels	Load Wheels	Steer Wheels			
18 x 6 x 12 1/8 (457 x 152 x 308)	2100	1720	1870	1575	1525	1250	in.	6.0	18.0
							mm	152	457
18 x 7 x 12 1/8 (457 x 178 x 308)	2550	2100	2280	1910	1855	1520	in.	7.0	18.0
							mm	178	457
18 x 8 x 12 1/8 (457 x 203 x 308)	3000	2475	2680	2250	2180	1790	in.	8.0	18.0
							mm	203	457
18 x 9 x 12 1/8 (457 x 229 x 308)	3450	2850	3090	2600	2510	2060	in.	9.0	18.0
							mm	229	457
21 x 6 x 15 (533 x 152 x 381)	2350	1930	2100	1765	1710	1400	in.	6.0	21.0
							mm	152	533
21 x 7 x 15 (533 x 178 x 381)	2875	2350	2560	2150	2085	1710	in.	7.0	21.0
							mm	178	533
21 x 8 x 15 (533 x 203 x 381)	3375	2775	3025	2540	2455	2015	in.	8.0	21.0
							mm	203	533
22 x 8 x 16 (559 x 203 x 406.4)	3500	2875	3130	2625	2545	2085	in.	8.0	22.0
							mm	203	559
22 x 9 x 16 (559 x 229 x 406.4)	4050	3325	3600	3025	2930	2400	in.	9.0	22.0
							mm	229	559
22 x 12 x 16 (559 x 305 x 406.4)	5625	4625	5030	4225	4090	3350	in.	12.0	22.0
							mm	305	559
28 x 12 x 22 (711 x 305 x 559)	6740	5540	6020	5060	4900	4015	in.	12.0	28.0
							mm	305	711

Applications

Footprint