



MID-RANGE MATERIALS HANDLING RESILIENT

MASTERSOLID

Reliability in the Shape of a Tire

Mastersolid is designed to deliver good performance at a competitive price.

Mastersolid delivers a good total value of ownership. It's made from quality rubber compounds, has low rolling resistance, which reduces fuel costs and a wide tread pattern for good stability.

Mastersolid is available in most common sizes in both LOC and NON LOC and in Non-Marking.

PERFORMANCE DEFINED

TIRE LIFE

Trelleborg products guarantee **best in class** performance. This results in longer tire life, **additional hours of usage**, reduced downtime and lower maintenance costs.

ENERGY SAVING

Trelleborg is a **leading approved tire manufacturer to the OEMs**. We work closely with them to ensure we meet the requirements of energy consumption. This results in **reduced fuel costs** for our customers.

STABILITY

Trelleborg products are designed to have **large footprints** maximizing the contact area, leading to better stability and even tire wear.

COMFORT

Trelleborg understands the requirements of a **safe working environment**. Our products are designed to reduce vibration and keep noise to a **minimum level**. We follow the strictest regulations for work safety while providing a comfortable ride.

MID-RANGE MATERIALS HANDLING RESILIENT

MASTERSOLID

| Tire Size | Alternative Size | Rim Size | LOC | Tire Dimensions (in) | | Load Capacity (lbs) | | | Weight (lbs) |
|------------------|------------------------|----------|-----|----------------------|---------------|---------------------|------------------------------|----------------|--------------|
| | | | | Overall Diameter | Section Width | Static | Forklift trucks up to 15 mph | | |
| | | | | | | | Load Wheel | Steering Wheel | |
| 3.00-4 * | | 2.10-4 | | 9.8 | 3.3 | 650 | 560 | 430 | 8 |
| 3.00-4 * | | 2.50C-4 | | 9.8 | 3.3 | 650 | 560 | 430 | 8 |
| 4.00-8 | | 3.00D-8 | • | 15.9 | 4.1 | 2,425 | 2,095 | 1,610 | 24 |
| 15x4½-8 | 125/75-8 | 3.00D-8 | • | 14.8 | 4.1 | 2,670 | 2,295 | 1,765 | 19 |
| 5.00-8 | | 3.00D-8 | • | 18.1 | 4.5 | 3,640 | 3,120 | 2,405 | 34 |
| 16x6-8 | 150/75-8 | 4.33R-8 | • | 16.0 | 5.2 | 3,835 | 3,295 | 2,535 | 35 |
| 18x7-8 | 180/70-8 | 4.33R-8 | • | 17.9 | 5.7 | 5,490 | 4,730 | 3,640 | 44 |
| 140/55-9 | 15x5.5-9 | 4.00E-09 | • | 15.0 | 5.2 | 3,000 | 2,580 | 1,985 | 22 |
| 6.00-9 | | 4.00E-09 | • | 20.4 | 5.2 | 4,830 | 4,155 | 3,195 | 56 |
| 21x8-9 | 200/75-9 | 6.00E-09 | • | 20.6 | 6.6 | 7,055 | 6,075 | 4,675 | 71 |
| 6.50-10 | | 5.00F-10 | • | 22.6 | 5.8 | 5,995 | 5,160 | 3,970 | 77 |
| 200/50-10 | | 6.50F-10 | • | 18.0 | 7.3 | 6,325 | 5,445 | 4,190 | 51 |
| 23x9-10 | 225/75-10 | 6.50F-10 | • | 23.0 | 8.3 | 8,820 | 7,595 | 5,840 | 108 |
| 7.00-12 | | 5.00S-12 | • | 25.6 | 6.4 | 7,450 | 6,435 | 4,940 | 100 |
| 23x10-12 | 250/60-12 | 8.00G-12 | • | 22.9 | 9.0 | 9,655 | 8,310 | 6,395 | 105 |
| 27x10-12 | 250/75-12 | 8.00G-12 | • | 26.5 | 9.0 | 9,985 | 8,600 | 6,615 | 153 |
| 7.00-15 | 29x8-15 | 5.5-15 | • | 28.5 | 7.3 | 9,070 | 7,815 | 6,010 | 134 |
| 7.50-15 | | 5.5-15 | • | 29.7 | 7.4 | 9,985 | 8,600 | 6,615 | 152 |
| 7.50-15 | | 6.5-15 | • | 29.7 | 7.4 | 9,985 | 8,600 | 6,615 | 157 |
| 8.25-15 | | 6.5-15 | • | 32.4 | 8.0 | 12,145 | 10,470 | 8,045 | 203 |
| 28x9-15 | 225/75-15 (8.15-15) | 7.0-15 | • | 26.8 | 8.0 | 9,985 | 8,600 | 6,615 | 124 |
| 250-15 | 250/70-15 | 7.0-15 | | 28.3 | 8.3 | 12,145 | 10,460 | 8,045 | 149 |
| 250-15 | 250/70-15 | 7.5-15 | • | 28.3 | 8.3 | 12,145 | 10,460 | 8,045 | 152 |
| 300-15 | 315/70-15 | 8.0-15 | • | 32.4 | 9.8 | 14,980 | 12,895 | 9,920 | 253 |
| 465/55-20 | | 16.0-20 | | 40.5 | 18.3 | 29,960 | 23,810 | 19,840 | 684 |

SPECIAL COMPOUNDS AVAILABLE



Non-Marking

* Only available with Military tread pattern

TREAD PATTERNS



MS

Dealer Logo

Dealer Address and contact information



TRELLEBORG

TRELLEBORG.COM/WHEELS